

BRAKES

Spring Applied Brake - INTORQ BFK551

33008168

This spring-applied brake was developed as a dynamic or holding brake with emergency stop function. Due to its compact design, it can be easily integrated on the motor shaft in new or existing drives. Connection cables can be routed past the housing through recesses.



Features

- Completely assembled with integrated Torx® fastening screws
- Compact design with rotor and flange
- Simple mounting
- Manual release available for sizes 03/04/05
- Customization possible

| DESCRIPTION | VALUE |
|------------------------------|------------------------|
| Brake size | 04 |
| Torque | 1 Nm |
| Torque definition | M2/MK (dynamic) |
| Operation mode | Operating Brake |
| Nominal voltage | 205 V |
| Nominal power | 10.9 W |
| Max. switching energy per ES | 1200 J |
| Total work | 9000 kJ |
| Temperature range | -20...40°C |
| Max. rotation speed | 5000 min ⁻¹ |
| E-Stop rotation speed | 5000 min ⁻¹ |

| | |
|---------------------------------|-------------------|
| Backlash | - |
| Thermal class | F |
| IP Protection class | IP00,IP55 |
| Weight | 0.45 kg |
| Brake type | - |
| Armature type | - |
| Hub type | - |
| Hand release | - |
| Counter friction part | Flange |
| PWM control | possible |
| Outer diameter | 65 mm |
| Lenght | 31.8 mm |
| Keyway | 6,7,8,10 DIN 6885 |
| Pitch circle flange side | 58 mm |
| Product Line | BFK551 |

CONTACT

Sales Team Kendrion Villingen

+49 (0) 7721 877-1417

sales-villingen-ib@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/brakes/33008168>