

## BRAKES

# Permanent Magnet Brake - PM Line

86 61103H00-0011

The PM Line is a permanent magnet brake for direct current in which the braking effect is generated by a permanent magnetic field (system opened by electro-magnetic force). The brake thus acts in currentless state when switched off. To neutralize the braking effect, the permanent magnetic field is displaced by an opposing electromagnetic field. These brakes are particularly suitable for applications in the field of servomotors as holding brakes with emergency stop function.



### Features

- Safe, residual torque-free opening in any mounting position
- Backlash-free transmission of the braking torque

DESCRIPTION	VALUE
Brake size	03
Torque	0.4 Nm
Torque definition	M4 (static)
Operation mode	Holding Brake
Nominal voltage	24 V
Nominal power	6.2 W
Max. switching energy per ES	10 J
Number of emergency stops	500
Total work	5 kJ
Temperature range	-5°C...120°C
Max. rotation speed	16000 min <sup>-1</sup>
E-Stop rotation speed	3000 min <sup>-1</sup>
Backlash	0°
Thermal class	F
IP Protection class	IP00
Weight	0.07 kg
Brake type	611
Armature type	300
Hub type	-
Hand release	-
Counter friction part	-
PWM control	possible
Outer diameter	28 mm
Inner diameter	9 mm
Length	26.7 mm
Hub diameter	8 mm
Keyway	-
Pitch circle front side	22 mm
Product Line	PM Line

## **CONTACT**

Sales Team Kendrion Villingen

+49 (0) 7721 877-1417

[sales-villingen-ib@kendrion.com](mailto:sales-villingen-ib@kendrion.com)

## **PRODUCT**

<https://www.kendrion.com/en/productfinder/group/product/brakes/86-61103h00-0011>