

BRAKES

Spring Applied Brake - INTORQ BFK457

BFK457-16

Do you need a spring-applied brake that reliably fulfills your desired basic functionality and can quickly be put to work? Then the BFK457 is the perfect match! The integrated fastening screws and fixed air gap ensure that it is easy to install. Its compact design helps to reduce costs and minimize installation space.



- 6 Sizes
- Replaceable rotor
- Mounted hand release (optional)
- Designed for 100% duty cycle
- Available as noise reduced double-brake <50dB(A)

DESCRIPTION	VALUE
Brake Size	16
Torque	125 Nm
Torque definition	M2/MK (dynamic)
Operation mode	Holding Brake
Nominal voltage	24,205 V
Nominal power	55 W
Max. switching Energy per ES	36000 J
Number of Emergency stops	500
Temperature range	-20...40°C
Max. rotation speed	3600 min-1
E-Stop rotation speed	3600 min-1
Backlash	-
Thermal class	F
IP Protection class	IP00,IP55

Weight	10 kg
Brake type	-
Armature type	-
Hub type	-
Hand release	Optional
Counter friction part	Flange
PWM control	-
Outer diameter	190 mm
Lenght	80,5 mm
Hub diameter	38 mm
Keyway	25,30,35,38, DIN 6885
Pitch circle front side	170 mm
Pitch circle flange side	170 mm

CONTACT

Sales Team Kendrion Villingen

+49 (0) 7721 877-1417

sales-villingen-ib@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/brakes/bfk457-16>