

## BRAKES

# Spring Applied Brake - Servo Line

KS 10008A00-0001

The spring-applied brake of the Servo Line series was developed for integrated installation in servo motors. The holding brake with emergency stop function of the Servo Line is designed for both, A-side and B-side integrated installation in servo drives for dry running.



### Features

- Rated air gap tolerance is reduced to a few hundredths of a millimeter, providing enhanced power density
- Toothed hub-friction disc connection with minimal backlash
- Standard version suitable for flange mounting and face mounting
- Guaranteed minimum torque over life-time

DESCRIPTION	VALUE
Brake size	08
Torque	7.0 Nm
Torque definition	M4 (static)
Operation mode	Holding Brake
Nominal voltage	24 V
Nominal power	14.7 W
Max. switching energy per ES	140 J
Number of emergency stops	500
Total work	70 kJ
Temperature range	-15...120°C
Max. rotation speed	6500 min <sup>-1</sup>
E-Stop rotation speed	3000 min <sup>-1</sup>
Backlash	< 1°
Thermal class	F
IP Protection class	IP00
Weight	0.9 kg
Brake type	KS 100
Armature type	-
Hub type	Long
Hand release	-
Counter friction part	Flange
PWM control	possible
Outer diameter	78 mm
Inner diameter	22 mm
Length	37 mm
Hub diameter	20.5 mm
Keyway	-
Pitch circle front side	60 mm
Pitch circle flange side	71 mm

Product Line

Servo Line

## CONTACT

Sales Team Kendrion Villingen

+49 (0) 7721 877-1417

[sales-villingen-ib@kendrion.com](mailto:sales-villingen-ib@kendrion.com)

## PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/brakes/ks-10008a00-0001>