

COMPACT I/O

CIO CANopen 8DI/10DO/4AI-I/ 2AI-U/2AO-I/3AO-U/5Pt/2Thermo

611 220 87



The Kuhnke CIO compact I / O with CANopen fieldbus interface contains various digital and analog input and output signals in a compact housing for the DIN rail. The robust design allows the use in machine and apparatus construction.

- Compact control cabinet module
- Integrated I/Os: 8DI/10DO/4AI-I/2AI-U/2AO-I/3AO-U/5Pt/2Thermo
- CANopen fieldbus interface

DESCRIPTION	VALUE
Configuration	8DI/10DO/4AI-I/2AI-U/2AO-I/3AO-U/5Pt/2Thermo
Function	I/O system with CANopen field bus
Model	Control cabinet modul
Product status	Standard product
Field bus interfaces	CANopen
Interfaces	CANopen
Digital I/Os (integrated)	8 DI 5 ms, 10 DO 0,5A
Analogue I/Os (integrated)	4AI-I, 4AI-U, 2AO-I, 3AO-U, 5Pt100, 2Thermo
Type of connection	multi-pin plug connector
Status indication	system messages
Housing material	plastic tray with stainless steel cover
Dimensions (W x H x D)	170 mm x 115 mm x 48 mm
IP-Protection Class	IP 20
Supply voltage	24 V (-20% / +25%)

Operating temperature

0 ... +55 °C

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/compact-io/611-220-87>