

DIRECT-OPERATED SOLENOID VALVES**Solenoid Valve Type 64**

64.017

These valves can be supplied in a wide variety of standard versions, e.g.: in three different base shapes (standard, flange and screw-in base), with connection for plug-in socket prefabricated or with flying leads, as 2/2 way NC or 3/2 way NO/NC, also available as low watt version and with nominal orifice of 0.5, 1 or 1.5 mm. For plug-in sockets, current indication and erasing diode please see valve accessories.



DESCRIPTION	VALUE
Function	3/2-way NO
Pressure range	0 - 8 bar
Nominal orifice	1.0 mm
Type of pneumatic connection	M5
Kv-value	0.45 l/min
Size	16 mm
Actuation type	electrically actuated
Duty cycle	100 % ED
Type of electric connection	Plug-in socket
Medium	Filtered (5 µm), lubricated and non lubricated air
Nominal power	4.6 W
Nominal voltage	24 V DC
Returning mechanism	Spring
Protection class	IP65
Ambient temperature	-10 ... +50 °C
Valve type	Poppet valve
Materials	Base: Brass, seal: NBR

Actuation	directly controlled
Identification number	16616

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/direct-operated-solenoid-valves/64017>