

DIRECT-OPERATED SOLENOID VALVES

Solenoid Valve Type 64

64.071

These valves can be supplied in a wide variety of standard versions, e.g.: in three different base shapes (standard, flange and screw-in base), with connection for plug-in socket prefabricated or with flying leads, as 2/2 way NC or 3/2 way NO/NC, also available as low watt version and with nominal orifice of 0.5, 1 or 1.5 mm. For plug-in sockets, current indication and erasing diode please see valve accessories.



| DESCRIPTION | VALUE |
|------------------------------|--|
| Function | 3/2-way NC |
| Pressure range | 0 - 5 bar |
| Nominal orifice | 1.5 mm |
| Type of pneumatic connection | M5 |
| Kv-value | 0.7 l/min |
| Size | 16 mm |
| Actuation type | electrically actuated |
| Duty cycle | 100 % ED |
| Type of electric connection | Wire |
| Medium | Filtered (5 µm), lubricated and non lubricated air |
| Nominal power | 4.6 W |
| Nominal voltage | 24 V DC |
| Returning mechanism | Spring |
| Protection class | IP65 |
| Ambient temperature | -10 ... +50 °C |
| Valve type | Poppet valve |
| Materials | Base: Brass, seal: NBR |

| | |
|------------------------------|---------------------|
| Actuation | directly controlled |
| Identification number | 170069 |

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/direct-operated-solenoid-valves/64071>