

**DIRECT-OPERATED SOLENOID VALVES****Solenoid Valve Type 65**

65.120

These valves can be supplied in a wide variety of standard versions, e.g.: in three different base shapes (standard, flange and screw-in base), with connection for plug-in socket prefabricated or with flying leads, as 3/2 way NO/NC valve (2/2 way on request), also available as low watt version and with nominal orifice of 0.5, 1, 1.6 or 2 mm. For plug-in sockets, current indication and erasing diode please see valve accessories



DESCRIPTION	VALUE
Function	3/2-way NC
Pressure range	0 - 8 bar
Nominal orifice	1.0 mm
Type of pneumatic connection	G1/8
Kv-value	0.45 l/min
Size	20 mm
Actuation type	electrically actuated
Duty cycle	100 % ED
Type of electric connection	Plug-in socket
Medium	Filtered (5 µm), lubricated and non lubricated air
Nominal power	5.0 W
Nominal voltage	24 V DC
Returning mechanism	Spring
Protection class	IP65
Ambient temperature	-10 ... +60 °C
Valve type	Poppet valve
Materials	Base: Brass, seal: NBR

<b>Actuation</b>	directly controlled
<b>Identification number</b>	12170

## CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

[sales-ics@kendrion.com](mailto:sales-ics@kendrion.com)

## PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/direct-operated-solenoid-valves/65120>