

LINEAR SOLENOIDS

Frame Linear Solenoid LCL 30x35

43030003

The D-frame solenoid LCL is characterized by a compact design, low power consumption and short switching times. A long service life is promoted by the precision steel tube housing and maintenance-free armature bearings. The frame solenoid can be installed in any position, with the force preferably being applied in the axial direction only. It is fastened via threaded holes on the side or on the face.

As standard, the frame linear solenoid has a chemically nickel-plated armature and a plastic-molded solenoid coil and has protection class IP 40. Versions with bellows achieve protection class IP54.

Other voltages are possible on request.



DESCRIPTION	VALUE
Duty cycle	100 %
Power consumption	10.9 W
Stroke	15 mm
Initial force	3 N
Nominal voltage	24 V
End force	8.5 N
Return spring	No
Dimensions (length, width, height)	50 x 30 x 35 mm
Length	50
Width	30
Height	35
Design	No
Protection class	IP 40

Thermal class	B 130
Connection	Leads / cable
Solenoid weight	250 g
Armature weight	55 g
Product Line	Single Stroke Linear Solenoids

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/linear-solenoids/43030003>