

LINEAR SOLENOIDS

Frame Linear Solenoid LCL 48x60

43050004

The D-frame solenoid LCL is characterized by a compact design, low power consumption and short switching times. A long service life is promoted by the precision steel tube housing and maintenance-free armature bearings. The frame solenoid can be installed in any position, with the force preferably being applied in the axial direction only. It is fastened via threaded holes on the side or on the face.

As standard, the frame linear solenoid has a chemically nickel-plated armature and a plastic-molded solenoid coil and has protection class IP 40. Versions with bellows achieve protection class IP54.

Other voltages are possible on request.



DESCRIPTION	VALUE
Duty cycle	100 %
Power consumption	20.7 W
Stroke	25 mm
Initial force	13 N
Nominal voltage	24 V
End force	37 N
Return spring	No
Dimensions (length, width, height)	75 x 48 x 60 mm
Length	75
Width	48
Height	60
Design	No
Protection class	IP 40

Thermal class	B 130
Connection	Plug
Solenoid weight	1160 g
Armature weight	230 g
Product Line	Single Stroke Linear Solenoids

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/linear-solenoids/43050004>