

## LINEAR SOLENOIDS

### Linear Solenoid H6246

H6246-F-24V DC 100 ED

Open frame solenoid as **Push type solenoid** with conical face armature. Our preferred types are available in small quantities from stock. Other versions or other voltages are available on request. More information can be found in the download area.



| DESCRIPTION                        | VALUE                          |
|------------------------------------|--------------------------------|
| Duty cycle                         | 100 %                          |
| Power consumption                  | 11 W                           |
| Stroke                             | 15 mm                          |
| Initial force                      | 0.8 N                          |
| Nominal voltage                    | 24 V                           |
| End force                          | 18 N                           |
| Return spring                      | No                             |
| Dimensions (length, width, height) | 44 x 38 x 50 mm                |
| Length                             | 44                             |
| Width                              | 38                             |
| Height                             | 50                             |
| Design                             | No                             |
| Protection class                   | IP 00                          |
| Thermal class                      | B, 130                         |
| Connection                         | 10 cm lead                     |
| Solenoid weight                    | 320 g                          |
| Armature weight                    | 45 g                           |
| Product Line                       | Single Stroke Linear Solenoids |

## CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

[sales-ics@kendrion.com](mailto:sales-ics@kendrion.com)

## PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/linear-solenoids/h6246-f-24v-dc-100-ed>