

**LINEAR SOLENOIDS**

# High Power Linear Solenoid RM040

RM040W-OBOO-F-24V DC 100 ED

Linear solenoid in enclosed design with maintenance-free armature bearing for maximum durability. Available as combi type solenoid, also with integrated return spring. Starting with size RM040 of the modular system, the heavy duty solenoids are available in a wide range of specifications, including splash-proof models. Our preferred types are available in small quantities from stock. Other versions or other voltages are available on request. More information can be found in the download area.



DESCRIPTION	VALUE
Duty cycle	100 %
Power consumption	11 W
Stroke	8 mm
Initial force	6 N
Nominal voltage	24 V
End force	18 N
Return spring	No
Dimensions (length, width, height)	40 x 40 x 45 mm
Length	40
Width	40
Height	45
Design	No
Protection class	IP 40
Thermal class	F, 155
Connection	10 cm lead
Solenoid weight	380 g

Armature weight	60 g
Product Line	High Power Linear Solenoids

## CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

[sales-ics@kendrion.com](mailto:sales-ics@kendrion.com)

## PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/linear-solenoids/rm040w-oboo-f-24v-dc-100-ed>