

SOLENOID PINCH VALVES

Power Pinch Valve PPV 7 with manual release

PPV7 NC 24 VDC 100 ED

Electromagnetically operated pinch valve PPV 7 (NC) with high flow rates and precise control.

The 2/2-way NO (normally closed) pinch valve clamps tubes with a diameter up to 7mm and depending on the used material (PVC / Silicone) up to 1.5mm wall thickness. It has a clamping force of 42N.

Optional:

- Manual release



Want to learn more about how the Power Pinch Valves work and their applications?

[Visit our POWER PINCH VALVE website](#)

| DESCRIPTION | VALUE |
|-------------------|---------------|
| Solenoid weight | 1300 g |
| Dimensions | 84 x 53 x 146 |
| Design | 2/2 way |
| Mode of action | NC |
| Diameter hose | 4 to 7 mm |
| Nominal voltage | DC 24 V |
| Duty cycle | 100 % |
| Power consumption | 18 W |
| Thermal class | B 130 °C |
| Clamping force | 42 N |
| Connection | Lead 20 cm |

CONTACT

Sales Team Kendrion Malente

+49 (0) 4523 402-0

sales-ics@kendrion.com

PRODUCT

<https://www.kendrion.com/en/productfinder/group/product/solenoid-pinch-valves/ppv7-nc-24-vdc-100-ed>