

**VALVES, PNEUMATICALLY AND MECHANICALLY ACTUATED**

# Mechanically Actuated Valve Type 46

46.001

Because of its hexagonal shape, this 3/2 way NC valve requires only a minimum of space.



DESCRIPTION	VALUE
Function	3/2-way NC
Pressure range	0 - 12 bar
Nominal orifice	2 mm
Kv-value	1.65 l/min
Actuation type	mechanically actuated, toggle lever
Stroke	2 mm
Medium	Filtered (5 µm), lubricated and non lubricated air
Type of pneumatic connection	M5
Returning mechanism	Spring
Ambient temperature	-10 ... +70 °C
Valve type	Poppet valve
Materials	Housing: brass, plunger: CrNi steel (corrosion-resistant), seal: NBR (oil-resistant)
Actuation	directly controlled
Accessories	Mounting flange (order no. 43.010-1), mounting bracket (oder no. 43.010-2)
Identification number	12124

## **CONTACT**

Sales Team Kendrion Malente

+49 (0) 4523 402-0

[sales-ics@kendrion.com](mailto:sales-ics@kendrion.com)

## **PRODUCT**

<https://www.kendrion.com/en/productfinder/group/product/valves-pneumatically-and-mechanically-actuated/46001>