

Solenoid Valves

Fluid Technology

Fluid Isolation Solenoid Valves Series 97

High flow rates and optimal media resistance

Discover our direct operated fluid isolation solenoid valves Series 97, which is convinced through their compact design and realizable high flow rates. Due to the pressure compensated design these valves have a low power consumption compared to the orifice size of 3.5 mm (depending on pressure range). The flow optimized inner design ensures good flushing properties in e.g. cleaning processes.

Materials in contact with the medium as well as electrical and pneumatic connections can be adapted according to customer requirements.

Properties

- High flow rates (orifice of 3.5 mm)
- Pressure compensated design for low power consumption
- Good flushing properties
- Adaption of technical data on request
- Applications in e. g. Medical Technology, Analysis Technology and Machine Building



Technical Data	Fluid Isolation Solenoid Valve Series 97
Nominal voltage (U_{nom})	24 V DC or 12 V DC
Power consumption (P_{nom})	≤ 4.6 W
Pressure range (p)	-0.9...3.5 bar (up to 8 bar on request)
Orifice size	approx. 3.5 mm
Kv-value	max. 3.5 l/min
Materials in media contact	Sealings: either EPDM, NBR or FKM; Housing: PPSU or PA Materials listed according to FDA and UL, drinking water approval KTW/W270
Protection classification	IP 65 (with plug-in socket and occupied pneumatic connections or leads)
Pneumatic connection	Flange or push-in connectors (either 4 mm or 6 mm)
Electrical connection	Flat plug receptacles 6.3 x 0.8, industry standard fitting plug-in connector type B according to EN 60529 (not included in delivery) or leads
Functions	3/2 way NC/NO, 2/2 way NC/NO, 3/2 way multifunctional
Dimensions (h x w x d)	68 mm x 22 mm x 30 mm (flange version)
Nominal voltage (U_{nom})	24 V DC or 12 V DC

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders.