

Kuhnke Econo PLC

Control Technology

Kuhnke Econo 206 Compact PLC

The fanless PLC with iMX6 processor technology combines compactness with longevity and performance. The device has an integrated flash disk and an easily accessible SD card slot. USB interfaces allow the use of additional change-over memories or external peripherals.

The compact controller is designed for short PLC cycle times.

State-of-the-art fieldbus interfaces, CODESYS V3 and non-volatile memory enable the use of the Kuhnke Econo 206 as a cost-effective industrial controller for machines and systems.

As user interface, we recommend our touch panels Kuhnke Vico.



Features

- Fanless i.MX6 processor technology
- Industry standard interfaces
- CODESYS V3 with EtherCAT® Configurator, RTC
- upgradeable with CODESYS Softmotion
- Stable, compact housing



Technical Data	Kuhnke Econo 206
Model	CODESYS compact control for the control cabinet
Processor	Freescale i.MX6X, 1 GHz
RAM / Non-volatile memory	512 MB RAM / integrated flash memory
Drives	Flash disk 256 MB, SD(HC)-Card Slot
Operating system / Software	Operating system: Windows Embedded Compact 2013 Application: CODESYS V3 Soft PLC, optional with WebVisu, optional with CODESYS Softmotion (CNC)
Interfaces	2 x Ethernet 10/100Mbit, 1 x RS-232, 1 x RS-485 galvanically isolated 2 x USB 2.0 host, 1 x CAN, 1 x CAN galvanically isolated
Network	2 x Ethernet 10/100/1000 Mbit – RJ45
Fieldbus interface	2 x CANopen, Modbus RTU/TCP, EtherCAT® over Ethernet, optional OPC UA Server
Overall size (W x H x D)	47 x 154 x 105 mm (without connector and mounting plate)
Housing	IP 20, Stainless steel, heat sink made of aluminum
Operating temperature	0 ... 60°C
Supply voltage	24 V DC (± 20%)

NH3919

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders. EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Safety over EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Microsoft®, Windows® and the Windows® Logo are registered trademarks of Microsoft Corporation in the USA and other countries. At www.plcopen.org you will find more information about PLCopen Organisation. CODESYS is a product of 3S-Smart Software Solutions GmbH. CiA® and CANopen® are registered community trademarks of CAN in Automation e.V.