

## Kuhnke FIO Controller

## Control Technology

### Kuhnke FIO Controller 116 PROFINET IRT Mini IPC Controller as PROFINET IO Device


The Kuhnke FIO Controller 116 PROFINET-IRT is a mini-IPC basing on ARM with integrated CODESYS PLC. It is able to exchange data with other systems via industrial Ethernet and RS232. In addition, a built-in SD-card slot and a USB-interface allow local storage of process data. As far as mechanic properties and form factor are concerned, the controller matches the FIO I/O modules, which can be attached directly to form a mechanically and electrically homogenous unit.

It can be easily integrated by the number of interfaces (Industrial Ethernet, RS232, CAN), supported fieldbuses and attachable communication modules into existing control concepts. Furthermore, the Controller can exchange data with existing PROFINET IO Controllers via the left side appendix as a PROFINET IO Device. The Controller 116 always supports Modbus TCP and RTU master functionality. By using an additional extender module, the control of remote EtherCAT slaves is possible, too. Offering the OPC UA interface the Controller is the perfect device for industry 4.0 communication.



#### Features

- Easy integration in PROFINET® systems
- To be extended with FIO modules
- CODESYS V3 with EtherCAT®
- Optional: CODESYS SoftMotion
- OPC UA interface



Technical Data	Kuhnke FIO Controller 116 IRT
Processor	i.MX6 SoloX Freescale 1 GHz
RAM / nonvolatile memory	256 MB / 128 kB storage in Flash
Drive	256 MB internal Flash memory, SD(HC)-card slot
Software	Application: CODESYS V3 Soft SPS optional with SoftMotion WebVisu and SoftMotion CNC + Robotics on request
Interfaces	1 x RS232, 1 x USB 2.0, 1 x CAN (galvanically isolated)
Network	1 x Ethernet 10/100 Mbit – RJ45, OPC UA (Server)
Field bus interface	CANopen® Master Modbus TCP Master (via Ethernet) und Modbus RTU Master (via RS232) EtherCAT® E-Bus-Interface, extern via Extender module 2 x PROFINET® IO Device (256 Byte In/ 256 Byte Out via Ethernet switch)
Integrated I/Os	1 x DI 1ms
Housing (W x H x D)	Aluminium, plastic housing 42 x 120 x 90 mm
Mounting	35 mm DIN Rail
Supply voltage	24 V DC / (19.2 ... 28.8), Power consumption approx. 3.5 W (@ 24 V DC)
Operating temperature	0 °C...+55 °C
Cyber Security, CRA	In Progress
Approvals / Standards	PROFINET IRT, CE (Industry), cULus, IEC 61131-2, IEC 61000-6-4, IEC 61000-6-2

We reserve the rights of modification, omission, error with respect to the products. Illustrations similar. All rights reserved by the individual copyright holders. EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Safety over EtherCAT® is registered trademark and patented technology, licensed by Beckhoff Automation GmbH, Germany. Microsoft®, Windows® and the Windows® Logo are registered trademarks of Microsoft Corporation in the USA and other countries. At [www.plcopen.org](http://www.plcopen.org) you will find more information about PLCOpen Organisation. CODESYS is a product of 3S-Smart Software Solutions GmbH. CiA® and CANopen® are registered community trademarks of CAN in Automation e.V. OPC UA is a registered trademark of OPC Foundation. PROFINET® is registered trademarks of PROFIBUS and PROFINET International (PI). Linux® is the registered trademark of Linus Torvalds in the United States and/or other countries.